

BHTS ZZ C4 200°



Bearing BHTS ZZ C4 200°

The BHTS ZZ C4 200° ball bearings are developed based on the structure of a standard bearing but with appropriate treatment of stabilization, radial clearance, greases and ZZ shields which make them suitable for operation from -30° to +200°.

alternative to : SNR: FT 150 ZZ - HT 200 ZZ SKF : ZZ C3 GJN NTN : TS3 C4

BHTS 2RS C4 VT 200°



Bearing BHTS 2RS C4 VT 200°

The BHTS 2RS C4 VT 200° are designed based on the dimensions of a standard bearing but with appropriate treatment of stabilization, radial clearance, greases and special Viton plates which make them suitable to operate from 30 to 200 °.

alternative to : SNR: FT 150 - HT 200 SKF : ZZ C3 GJN NTN : TS3 C4 FAG: S0 - S1

BHTS ZZ 280°



Bearing BHTS ZZ 280°

The BHTS ZZ 280° ball bearings are designed on the dimensions of a standard bearing but with treatments of stabilization, surface treatment, radial clearance, grease and special shield that make them suitable for operation from -30° to +280°.

alternative to : SNR: F604 SKF : VA 201 ZZ - VA 216 FAG: S2 - S3 SWC : HT ZZ

BHTS 2RS VT 250°-280°



Bearing BHTS VT 250°-280°

The BHTS VT 250°-280° ball bearings are designed on the dimensions 2 of a standard bearing but with treatments of stabilization, surface treatment, radial clearance, greases and special Viton seals which make them suitable for operation from -30 ° to between +250° and +280°.

BHTS ZZ GR CG 350°



Bearing BHTS ZZ GR CG 350°

The BHTS ZZ GR CG 350° ball bearings are designed on the dimensions of a standard bearing but with treatments of stabilization, surface treatment, radial clearance and a special cage made of graphite, which make them suitable for operation from -50 ° to +350°.

alternative to : SKF : VA 228 / VA 208

BHT 320°-350°



Bearing BHT 320°-350°

The BHT 320°-350° ball bearings are designed on the dimensions of a standard bearing but with treatments of stabilization, surface treatment, radial clearance and molybdenum grease that make them suitable for operation from -30° to +320°.

alternative to : SNR: F600 SKF : VA 201 Open - FAG: S2 - S3 SWC : HT Open

BHT FB 400°



Bearing BHT FB 400°

The BHT FB 400° bearings are designed on the dimensions of a standard bearing but with treatments of stabilization, surface treatment, radial clearance and full ball fitting that make them suitable for operation from -30° to +400°.